



WAAS CH 40339 W35A	APP CRS 350°	Rwy Idg TDZE 5885 Apt Elev 5885
--	------------------------	---

RNAV (GPS) RWY 35R

CENTENNIAL (APA)

RNP APCH. ▼ Circling Rwy 35L NA at night. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -21°C or above 54°C. For inop ALS, increase LNAV Cats C/D visibility to 1½ SM. ▲		MALSR 	MISSED APPROACH: (Do not exceed 240K until BPUTN) Climb to 8200 then climbing left turn to 9600 direct BPUTN and hold.	
ATIS 120.3	DENVER APP CON 132.75 269.3	CENTENNIAL TOWER 118.9	GND CON 121.8	CLNC DEL 128.6



8200	9600	BPUTN	8000	7060	9000
↑		↶	↷	↷	↷
LECEP		RONNI	JIDOG	FIRPI	
2.3 NM to RW35R		3.4 NM to RW35R	3.4 NM to RW35R	3.10°	
1.4 NM to RW35R		0.9 NM	1.1 NM	GP 3.10°	
1.4 NM		0.9 NM	1.1 NM	TCH 51	
CATEGORY		A	B	C	D
LPV DA		6085-½	200 (200-½)		
LNAV/VNAV DA		6324-¾	439 (500-¾)		
LNAV MDA		6380-½	495 (500-½)	6380-1	495 (500-1)
CIRCLING		6400-1 515 (600-1)	6540-1 655 (700-1)	6740-2½ 855 (900-2½)	6760-2¾ 875 (900-2¾)