ILS or LOC/DME RWY 35

MONROE COUNTY (BMG)


LOC I-BMG	APP CRS	Rwy Idg	6500
108.3	354°	TDZE	844
		Apt Elev	846


Circling to Rwy 6/24 NA at night. When local altimeter setting not received, use Terre Haute Rgnl altimeter setting; increase S-ILS 35 DA to 1165 and all MDA 140 feet and increase S-ILS 35 all Cats visibility ¼ SM, S-LOC 35 Cat C and D and Circling Cat C and D visibility ½ SM. For inoperative MALSR when using Terre Haute Rgnl altimeter setting: increase S-ILS 35 all Cats visibility to 1¼ miles. DME from OOM VORTAC. Simultaneous reception of I-BMG and OOM DME required.


MALSR

MISSED APPROACH: Climb to 2000 then climbing left turn to 2500 direct OOM VORTAC and hold.

ASOS	HULMAN APP CON	BLOOMINGTON TOWER★	GND CON	UNICOM
134.525	128.025 339.8	120.775 (CTAF) L	121.9	122.95







CATEGORY	A	B	C	D
S-ILS 35	1044-½ 200 (200-½)			
S-LOC 35	1420-½ 576 (600-½)		1420-1 576 (600-1)	1420-1¼ 576 (600-1¼)
CIRCLING	1420-1 574 (600-1)		1420-1½ 574 (600-1½)	1620-2½ 774 (800-2½)

FAF to MAP 5 NM

Knots	60	90	120	150	180
Min:Sec	5:00	3:20	2:30	2:00	1:40

EC-2, 22 FEB 2024 to 21 MAR 2024
EC-2, 22 FEB 2024 to 21 MAR 2024

RNAV (GPS) RWY 17

MONROE COUNTY (BMG)


WAAS CH 56412 W17A	APP CRS 174°	Rwy Idg 6500 / TDZE 845 / Apt Elev 846


RNP APCH.

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 47°C (116°F). Rwy 17 helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Terre Haute Rgnl altimeter setting and increase all DA 121 feet and all MDA 140 feet. Increase LPV all Cats, LNAV/VNAV all Cats, LNAV Cat C/D visibility ½ mile.


MISSED APPROACH: Climb to 3000 direct ALFRD and hold.

ASOS	HULMAN APP CON	BLOOMINGTON TOWER ★	GND CON	UNICOM
134.525	128.025 339.8	120.775 (CTAF) L	121.9	122.95





CATEGORY	A	B	C	D
LPV DA	1229-1¼ 384 (400-1¼)			
LNAV/VNAV DA	1404-2 559 (600-2)			
LNAV MDA	1460-1 614 (700-1)		1460-1¾ 614 (700-1¾)	1460-2 614 (700-2)



MIRL Rwy 6-24 L
HIRL Rwy 17-35 L
REIL Rwy 17 L

EC-2, 22 FEB 2024 to 21 MAR 2024
EC-2, 22 FEB 2024 to 21 MAR 2024

RNAV (GPS) RWY 24

MONROE COUNTY (BMG)


APP CRS	Rwy Idg	3576
244°	TDZE	841
	Apt Elev	846

RNP APCH.


T A Rwy 24 helicopter visibility reduction below 1 SM NA. Procedure NA at night. When local altimeter setting not received use Terre Haute Rgnl altimeter setting and increase all MDA 140 feet; increase LNAV Cat C/D ¼ mile.


MISSED APPROACH: Climb to 3000 direct OXDOH WP and hold.

ASOS	HULMAN APP CON	BLOOMINGTON TOWER ★	GND CON	UNICOM
134.525	128.025 339.8	120.775 (CTAF) L	121.9	122.95



ELEV 846	TDZE 841





CATEGORY	A	B	C	D
LNAV MDA	1320-1	479 (500-1)	1320-1¼ 479 (500-1¼)	1320-1½ 479 (500-1½)

MIRL Rwy 6-24 L
HIRL Rwy 17-35 L
REIL Rwy 17 L

EC-2, 22 FEB 2024 to 21 MAR 2024
EC-2, 22 FEB 2024 to 21 MAR 2024

RNAV (GPS) RWY 35

MONROE COUNTY (BMG)

WAAS	APP CRS		
CH **72812**	**354°**	Rwy Idg	**6500**
W35A		TDZE	**844**
		Apt Elev	**846**

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 47°C (116°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Terre Haute Rgnl altimeter setting; increase LPV DA to 1165, LNAV/VNAV DA to 1465 and all MDA 140 feet and increase LPV all Cats, LNAV Cat C, D visibility ¼ SM, LNAV/VNAV all Cats and Circling C and D visibility ½ SM. For inoperative MALSR when using Terre Haute Rgnl altimeter setting: increase LPV all Cats visibility ½ mile. Baro-VNAV and VDP NA when using Terre Haute Rgnl altimeter setting. Circling to Rwy 6/24 NA at night.

MALSR

MISSED APPROACH: Climb to 3000 direct ITYEF and hold.

ASOS	HULMAN APP CON	BLOOMINGTON TOWER ★	GND CON	UNICOM
134.525	**128.025 339.8**	**120.775** (CTAF) L	**121.9**	**122.95**

MISSED APCH FIX

4 NM 174° 354° ITYEF

Procedure NA for arrivals at OOM VORTAC via V305 northeast bound.

1199 1339 1253 982± 1092 882 HOOSIER OOM 1452

RW35 1047± 1086± 3000 to ALFRD 174° (11.7)

(FAF) NITTE 354° 2500 (6.5)

MSA RW35 25 NM 3100

CHARLES DEAM WILDERNESS AREA

3100 251° (14) HOUSE

BUNKA 3000 113° (23.5)


Procedure NA for arrivals at BUNKA via V243 northbound.


3000 NoPT 084° (5) (IAF) BEWHY

3000 NoPT 264° (5) (IAF) FODCU

(IF/IAF) ALFRD 354° 174° 4 NM

ELEV 846 TDZE 844





CATEGORY	A	B	C	D
LPV DA	1044-½ 200 (200-½)			
LNAV/VNAV DA	1344-1¼ 500 (500-1¼)			
LNAV MDA	1300-½ 456 (500-½)		1300-¾ 456 (500-¾)	1300-1 456 (500-1)
CIRCLING	1380-1 534 (600-1)	1400-1 554 (600-1)	1400-1½ 554 (600-1½)	1620-2½ 774 (800-2½)

EC-2, 22 FEB 2024 to 21 MAR 2024
EC-2, 22 FEB 2024 to 21 MAR 2024

RNAV (GPS) RWY 6

MONROE COUNTY (BMG)

APP CRS	Rwy Idg	3494
064°	TDZE	840
	Apt Elev	846


RNP APCH.


NA

Procedure NA at night.
Rwy 6 helicopter visibility reduction below 1 SM NA.


MISSED APPROACH: Climb to 3000 direct IJPOV and hold.

ASOS	HULMAN APP CON	BLOOMINGTON TOWER ★	GND CON	UNICOM
134.525	128.025 339.8	120.775 (CTAF) L	121.9	122.95





CATEGORY	A	B	C	D
LNAV MDA	1300-1 460 (500-1)		1300-1¼ 460 (500-1¼)	1300-1½ 460 (500-1½)



MIRL Rwy 6-24 L
HIRL Rwy 17-35 L
REIL Rwy 17 L

EC-2, 22 FEB 2024 to 21 MAR 2024
EC-2, 22 FEB 2024 to 21 MAR 2024

VORTAC OOM 110.2 Chan 39	APP CRS 169°	Rwy Idg 6500 TDZE 846 Apt Elev 846


VOR RWY 17


MONROE COUNTY (BMG)


Helicopter visibility reduction below ¾ SM NA. Circling to Rwy 6/24 NA at night. When local altimeter setting not received use Terre Haute Rgnl altimeter setting; increase all MDA 140 feet; increase S-17 and Circling Cat C and D visibility ½ SM.

MISSED APPROACH: Climb to 1800 then climbing right turn to 2500 direct OOM VORTAC and hold.

ASOS	HULMAN APP CON ★	BLOOMINGTON TOWER ★	GND CON	UNICOM
134.525	128.025 339.8	120.775 (CTAF) L	121.9	122.95







CATEGORY	A	B	C	D
S-17	1560-1	714 (800-1)	1560-2 714 (800-2)	1560-2¼ 714 (800-2¼)
CIRCLING	1560-1	714 (800-1)	1560-2 714 (800-2)	1620-2½ 774 (800-2½)

MIRL Rwy 6-24 L
HIRL Rwy 17-35 L
REIL Rwy 17 L

EC-2, 22 FEB 2024 to 21 MAR 2024
EC-2, 22 FEB 2024 to 21 MAR 2024

VORTAC OOM	APP CRS	Rwy Idg	3494
110.2	058°	TDZE	840
Chan 39		Apt Elev	846


VOR/DME RWY 6


MONROE COUNTY (BMG)


Procedure NA at night. When local altimeter setting not received, use Terre Haute Rgnl altimeter setting and increase all MDA 140 feet and S-6 Cat C and D visibility ⅜ SM, Circling Cat C visibility ½ SM, and Circling Cat D visibility ¼ SM.

MISSED APPROACH: Climb to 2000 then climbing right turn to 3000 direct OOM VORTAC and hold.


ASOS	HULMAN APP CON	BLOOMINGTON TOWER ★	GND CON	UNICOM
134.525	128.025 339.8	120.775 (CTAF) L	121.9	122.95







CATEGORY	A	B	C	D
S-6	1300-1 460 (500-1)		1300-1⅜ 460 (500-1⅜)	
CIRCLING	1380-1 534 (600-1)	1400-1 554 (600-1)	1400-1½ 554 (600-1½)	1620-2½ 774 (800-2½)



MIRL Rwy 6-24 L
HIRL Rwy 17-35 L
REIL Rwy 17 L

EC-2, 22 FEB 2024 to 21 MAR 2024
EC-2, 22 FEB 2024 to 21 MAR 2024